


Diversion Down. L 1000 mm

09.8001.40 - White

Electro-mechanical profile for indoor application with integrated direct linear light element for surface or suspended installation. Lengths from 1 to 2,5m. Fixation by a joint with power kit. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included.




Main specifications

Lamp category	LED	Mountings	Surface and suspension
Power (W)	13.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	634		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	62



Beam Angle:	62°		
h(m)	E(lx)	D(m)	
1	335	1.21	
2	84	2.41	
3	37	3.62	
4	21	4.82	
5	13	6.03	

Luminous flux luminaire
634 lm


Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1- 10V, Electronic dimmable DALI		

Emergency

Without

Certification / Marking



Physical

Color	White
Orientation	Fixed
Weight (kg)	0.56
Length (mm)	1000

Diversion Down. L 1000 mm



Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9416



Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9426



Casambi Broadcast. Remote Installation
60.9392