



## Diversion Down. L 2000 mm

■ 09.8004.CZ - Bronze

Electro-mechanical profile for indoor application with integrated direct linear light element for surface or suspended installation. Lengths from 1 to 2,5m. Fixation by a joint with power kit. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Surface and suspension
<b>Power (W)</b>	28W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	796		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	54
<b>Beam angle C90-270 (°)</b>	102
<b>Efficiency (lm/W)</b>	29



<b>Beam Angle:</b>	54°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	539	1.01	
2	135	2.02	
3	60	3.03	
4	34	4.04	
5	22	5.06	


Luminous flux luminaire  
796 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Bronze
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.14
<b>Length (mm)</b>	2000



## Diversion Down. L 2000 mm



---

24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V  
60.9426



---

24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V  
60.9416



---

24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V  
60.9361



---

Casambi Controller 220-240V. Remote Installation  
60.9392