


## Diversion Down. L 2500 mm

09.8006.40 - White

Electro-mechanical profile for indoor application with integrated direct linear light element for surface or suspended installation. Lengths from 1 to 2,5m. Fixation by a joint with power kit. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Surface and suspension
<b>Power (W)</b>	34.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	1584		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	62




<b>Beam Angle:</b>	62°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	836	1.21	
2	209	2.41	
3	93	3.62	
4	52	4.82	
5	33	6.03	

Luminous flux luminaire  
1584 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Certification / Marking



### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1428
<b>Length (mm)</b>	2500

## Diversion Down. L 2500 mm



---

Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V  
60.9361



---

Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V  
60.9416



---

Remote power supply. Dimmable through DALI protocol. 120W 110/240V  
60.9426



---

Casambi Broadcast. Remote Installation  
60.9392