

**Diversion Down. L 2500 mm****■ 09.8007.14 - Black**

Electro-mechanical profile for indoor application with integrated direct linear light element for surface or suspended installation. With lengths varying from 1 to 2.5m (distance between ball joint centers). Fixation by a joint with power kit. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system....


Electro-mechanical profile for indoor application with integrated direct linear light element for surface or suspended installation. With lengths varying from 1 to 2.5m (distance between ball joint centers). Fixation by a joint with power kit. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included.

**Main specifications**

<b>Lamp category</b>	LED	<b>Mountings</b>	Surface and suspension
<b>Power (W)</b>	35W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	924		

**Optical**


<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	52
<b>Beam angle C90-270 (°)</b>	101
<b>Efficiency (lm/W)</b>	26



Beam Angle: 52°

h(m)	E(lx)	D(m)
1	666	0.97
2	166	1.93
3	74	2.90
4	42	3.87
5	27	4.84

Luminous flux luminaire  
924 lm

**Electrical**

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
<b>Emergency</b>	Without		

**Physical**

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1428
<b>Length (mm)</b>	2500

**Note**

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz. In the case of the version without Spots, drivers with higher switching frequency, up to 2Khz, can be used. The profile's length measurement corresponds to the distance between the centers of the suspension joints. To install a profile of length L, the distance between joints coincides with the indicated measurement L, but the profile is a few centimeters smaller.



**Diversion Down. L 2500 mm**



Suspension joint for surface  
installation  
06.5303.14



Surface feed box for ceiling  
installation. 24V. Driver included 1-10V  
/ 57W  
06.5312.14



Recessed/surface joint  
06.5305.14



Feed recessed joint rose. 24V.  
06.5306.14



Suspension joint  
06.5301.14



Suspension feed box for surface  
installation. 24V. Driver included DALI /  
57W  
06.5314.14



Surface feed box for ceiling  
installation. 24V. Driver included DALI /  
57W



Feed suspension joint with rose for  
recessing. 24V  
06.5302.14



Surface feed box for ceiling installation. 24V. Driver included  
CASAMBI / 57W



Feed recessed joint. 24V  
06.5304.14



Suspension feed box for surface  
installation. 24V. Driver included 1-10V  
/ 57W  
06.5310.14



Feed suspension joint. 24V  
06.5300.14



24V Remote power supply. Dimmable  
through DALI protocol. 120W 110/240V  
60.9426



24V Remote power supply. Dimmable  
through 1/10V protocol. 120W 110/240V  
60.9416



Suspension feed box for surface  
installation. 24V. Driver included  
Casambi / 57W  
06.5311.14



24V Remote power supply. Dimmable  
through 1/10V protocol or Non  
Dimmable. 57W 220/240V  
60.9361



Casambi Controller 220-240V. Remote  
Installation  
60.9392