



Diversion Up&Down + Spots. L 2500 mm

09.8037.40 - White



Electro-mechanical profile for indoor application with integrated direct linear light element and space for two spots, for surface or suspended installation. Lengths from 1 to 2,5m. Fixation by fed suspension kit and suspended by a joint. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control...

Electro-mechanical profile for indoor application with integrated direct linear light element and space for two spots, for surface or suspended installation. Lengths from 1 to 2,5m. Fixation by fed suspension kit and suspended by a joint. Power kit and mechanical joint must be ordered separately. System controlled by 1-10V driver, DALI or Casambi. Broadcast control system. Dimmer not included. For single profile structures, suspended version, balance the spot to avoid profile tilting.




Main specifications

| | | | |
|-----------------------|-------|--------------------|------------------------|
| Lamp category | LED | Mountings | Surface and suspension |
| Power (W) | 53W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |
| Net lumen (lm) | 3074 | | |


Optical

| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 52 |
| Beam angle C90-270 (°) | 101 |
| Efficiency (lm/W) | 59 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 52° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 835 | 0.97 | |
| 2 | 209 | 1.93 | |
| 3 | 93 | 2.90 | |
| 4 | 52 | 3.87 | |
| 5 | 33 | 4.84 | |

Luminous flux luminaire
3074 lm



Electrical

| | | | |
|--------------------|--|-------------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable CASAMBI, Electronic dimmable 1- 10V, Electronic dimmable DALI | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------|
| Color | White |
| Orientation | Fixed |
| Weight (kg) | 1428 |
| Length (mm) | 2500 |

Note

Max. 2 spots not included.

Diversion Up&Down + Spots. L 2500 mm



Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9426



Casambi Controller 220-240V. Remote Installation
60.9392



Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9416