




Easy Kap 80 Plus Square Wall-Washer

Update

05.7437.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Elliptical lens included.




Main specifications

| | | | |
|-------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | CRI | 90 |
| Lamp category | LED | Net lumen (lm) | 844 |
| Power (W) | 13W | Mountings | Ceiling recessed |
| System power (W) | 13.4 | Environment | Indoor dry location |
| CCT (K) | 2700K | | |

Optical

| | |
|-------------------------------|-------------|
| LED type | LED array |
| Light distribution | Asymmetric |
| Optical type | Wall Washer |
| | Down |
| Beam angle (°) | 26 |
| Beam angle C90-270 (°) | 29 |
| UGRL | 21 |
| Efficiency (lm/W) | 62 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 26° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 1647 | 0.59 | |
| 2 | 412 | 1.19 | |
| 3 | 183 | 1.78 | |
| 4 | 103 | 2.37 | |
| 5 | 66 | 2.97 | |

Luminous flux luminaire
844 lm (EXTREME CUT OFF)

Electrical

| | | | |
|---------------------|---|-------------------------|---------|
| Voltage (V) | 18 | Emergency | Without |
| Current (mA) | 700 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |

Physical

| | | | |
|----------------------------|-------|---------------------------|--------|
| Color | Black | Lifespan (L70 B10) | L80B50 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 140 | | |
| Weight (kg) | 0.24 | | |

Easy Kap 80 Plus Square Wall-Washer



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 0/1-10V or push dimming
60.9188

Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W
60.9467

Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 0/1-10V or push dimming
60.8847



Non dimmable continuous current power supply. 15-30W, 220/240V – 50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable
60.9592

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207

Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 0/1-10V or push dimming
60.9222