


## Easy Kap 80 Square Adjustable Optic Flood - Dim-To-Warm

■ 03.4295.CU.LE - Copper

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	707
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	13W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2850K-1800K		
<b>CRI</b>	95		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	41
<b>Beam angle C90-270 (°)</b>	42
<b>Efficiency (lm/W)</b>	54



Beam Angle: 41°

h(m)	E(lx)	D(m)
1	1278	0.75
2	319	1.50
3	142	2.25
4	80	3.00
5	51	3.75

Luminous flux luminaire  
707 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Driver type</b>	Electronic dimmable 1-10V
<b>Voltage (V)</b>	33.00	<b>Emergency</b>	Without
<b>Current (mA)</b>	300	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		

### Physical

<b>Color</b>	Copper	<b>Tilt (°)</b>	20
<b>Orientation</b>	Adjustable	<b>Rotation (°)</b>	360
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	91		
<b>Weight (kg)</b>	0.24		

### Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

