


Easy Kap 80 Square Fixed Optic Medium - Dim-To-Warm

■ 03.4194.CU.LE - Copper

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

| | | | |
|------------------------|-------------|-----------------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 719 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 13W | Environment | Indoor |
| CCT (K) | 2850K-1800K | | |
| CRI | 95 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 27 |
| Beam angle C90-270 (°) | 28 |



Beam Angle: 27°


| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1914 | 0.48 |
| 2 | 478 | 0.95 |
| 3 | 213 | 1.43 |
| 4 | 120 | 1.90 |
| 5 | 77 | 2.38 |

Luminous flux luminaire
719 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|------------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 33.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic dimmable 1-10V | | |

Certification / Marking



Physical

| | | | |
|----------------------------|--------|---------------------------|----|
| Color | Copper | Spot diameter (mm) | 80 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 93 | | |
| Weight (kg) | 0.24 | | |

Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.