


## Easy Kap 80 Square Wall-Washer - Dim-To-Warm

■ 03.4198.BU.LE - Blue

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	632
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	13W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2850K-1800K		
<b>CRI</b>	95		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall Washer
	Down
<b>Beam angle (°)</b>	28
<b>Beam angle C90-270 (°)</b>	27
<b>Efficiency (lm/W)</b>	48



<b>Beam Angle:</b>	28°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	1214	0.68	
2	304	1.35	
3	135	2.03	
4	76	2.71	
5	49	3.39	

Luminous flux luminaire  
632 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Driver type</b>	Dimmable 1-10V
<b>Voltage (V)</b>	33.00	<b>Emergency</b>	Without
<b>Current (mA)</b>	300	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		

### Physical

<b>Color</b>	Blue
<b>Orientation</b>	Fixed
<b>Trim</b>	yes
<b>Recessed depth (mm)</b>	91
<b>Weight (kg)</b>	0.24

### Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

