

## Easy Kap Ø 105 Adjustable Optic Flood

■ 05.7012.BU - Blue


Recessed luminaire with LED light source. Remote transformer not included. Installation frame not necessary. Diffusing lens included.

### Main specifications

|                  |       |                |                  |
|------------------|-------|----------------|------------------|
| Number of heads  | 1     | CRI            | 90               |
| Lamp category    | LED   | Net lumen (lm) | 1753             |
| Power (W)        | 25.9W | Mountings      | Ceiling recessed |
| System power (W) | 25.9  | Environment    | Indoor           |
| CCT (K)          | 2700K |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 53        |
| Beam angle C90-270 (°) | 53        |
| Efficiency (lm/W)      | 67        |



|             |      |            |
|-------------|------|------------|
| Beam Angle: | 53°  |            |
|             | h(m) | E(lx) D(m) |
|             | 1    | 2610 1.01  |
|             | 2    | 652 2.01   |
|             | 3    | 290 3.02   |
|             | 4    | 163 4.03   |
|             | 5    | 104 5.04   |

Luminous flux luminaire  
1753 lm (EXTREME CUT OFF)

### Electrical

|              |   |                  |         |
|--------------|---|------------------|---------|
| Voltage (V)  | 34  | Emergency        | Without |
| Current (mA) | 650   | Insulation class | III     |
| Dimmable     | Yes   |                  |         |
| Driver       | Remote  |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V,<br>Electronic dimmable DALI |                  |         |

### Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Blue       | Tilt (°)           | 20  |
| Orientation         | Adjustable | Rotation (°)       | 360 |
| Trim                | yes        | Spot diameter (mm) | 111 |
| Recessed depth (mm) | 161        |                    |     |
| Weight (kg)         | 0,77       |                    |     |

## Easy Kap Ø 105 Adjustable Optic Flood



---

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/1000/1050mA-36W.  
60.9439



---

Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W  
700/750/800/900/1000/1050mA-36W  
60.9186



---

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207