

## Easy Kap Ø 50 Adjustable Optic Flood

■ 05.7217.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	447
Power (W)	7,3W	Mountings	Ceiling recessed
System power (W)	8.6	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	49
Beam angle C90-270 (°)	49
UGRL	15
Efficiency (lm/W)	51



Beam Angle:	49°		
	h(m)	E(lx)	D(m)
1	717	0.91	
2	179	1.82	
3	80	2.72	
4	45	3.63	
5	29	4.54	



Luminous flux luminaire  
447 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	35	Emergency	Without
Current (mA)	200	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		

### Physical

Color	Black	Tilt (°)	20
Orientation	Adjustable	Rotation (°)	360
Trim	yes	Spot diameter (mm)	59
Recessed depth (mm)	91	Lifespan (L70 B10)	L80B50
Weight (kg)	0.16		



## Easy Kap Ø 50 Adjustable Optic Flood



---

Continuous current power supply,  
dimmable DALI 2, 220/240V – 50/60Hz,  
200mA – 20W  
60.9604

Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200 mA – 8,5W /  
300 mA – 13W / 350 mA – 15W / 400 mA  
– 17,5W / 450 mA – 19,5W / 500 mA –  
22W  
60.9160

Continuous current power supply, 0-  
10V dimmable, 220/240V – 50/60Hz,  
200mA – 20W  
60.9483



---

Continuous current power supply.  
220/240V – 50/60Hz. Adjustable Current  
150 mA – 7,2W / 200 mA – 9,5W / 250 mA  
– 12W / 300 mA -14,5W / 350 mA  
-17W/400 mA – 19,5W / 450 mA -21,5W  
/500 mA – 24W. Mains or push dimming  
60.9421

Casambi Controller 220-240V. Remote  
Installation  
60.9392