

Easy Kap Ø 50 Adjustable Optic Medium

■ 05.7211.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 443 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 7.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 24 |
| Beam angle C90-270 (°) | 24 |
| Efficiency (lm/W) | 51 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 24° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 2018 | 0.43 | |
| 2 | 504 | 0.85 | |
| 3 | 224 | 1.28 | |
| 4 | 126 | 1.71 | |
| 5 | 81 | 2.13 | |



Luminous flux luminaire
443 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------|---|------------------|---------|
| Voltage (V) | 35 | Emergency | Without |
| Current (mA) | 200 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |

Physical

| | | | |
|---------------------|------------|--------------------|-----|
| Color | Black | Tilt (°) | 20 |
| Orientation | Adjustable | Rotation (°) | 360 |
| Trim | yes | Spot diameter (mm) | 59 |
| Recessed depth (mm) | 91 | | |
| Weight (kg) | 0,162 | | |



Easy Kap Ø 50 Adjustable Optic Medium



Continuous current power supply.
220/240V – 50/60Hz. Adjustable Current
150 mA – 7,2W / 200 mA – 9,5W / 250 mA
– 12W / 300 mA -14,5W / 350 mA
-17W/400 mA – 19,5W /450 mA -21,5W
/500 mA – 24W. Mains or push dimming
60.9421

Continuous current power supply, 0-
10V dimmable, 220/240V – 50/60Hz,
200mA – 20W
60.9483

Continuous current power supply,
dimmable DALI 2, 220/240V – 50/60Hz,
200mA – 20W
60.9604



Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160

Casambi Controller 220-240V. Remote
Installation
60.9392