


Easy Kap Ø 50 Fixed Optic Flood

■ 05.7202.GL - Gold

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 476 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 7.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 49 |
| Beam angle C90-270 (°) | 49 |
| Efficiency (lm/W) | 55 |



Beam Angle: 49°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 733 | 0.90 |
| 2 | 183 | 1.81 |
| 3 | 81 | 2.71 |
| 4 | 46 | 3.61 |
| 5 | 29 | 4.52 |

Luminous flux luminaire
476 lm (EXTREME CUT OFF)

Electrical

| | | | |
|---------------------|---|-------------------------|---------|
| Voltage (V) | 35 | Emergency | Without |
| Current (mA) | 200 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |

Physical

| | | | |
|----------------------------|-------|---------------------------|----|
| Color | Gold | Spot diameter (mm) | 59 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 100 | | |
| Weight (kg) | 0,136 | | |

Easy Kap Ø 50 Fixed Optic Flood



Continuous current power supply, 0-10V dimmable, 220/240V – 50/60Hz, 200mA – 20W
60.9483



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W
60.9160



Casambi Controller 220-240V. Remote Installation
60.9392



Continuous current power supply, dimmable DALI 2, 220/240V – 50/60Hz, 200mA – 20W
60.9604



Continuous current power supply. 220/240V – 50/60Hz. Adjustable Current 150 mA – 7,2W / 200 mA – 9,5W / 250 mA – 12W / 300 mA -14,5W / 350 mA -17W/400 mA – 19,5W / 450 mA -21,5W / 500 mA – 24W. Mains or push dimming
60.9421