


## Easy Kap Ø 50 Fixed Optic Medium

■ 05.7206.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 476                 |
| Power (W)        | 7,3W  | Mountings      | Ceiling recessed    |
| System power (W) | 8.6   | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 24        |
| Beam angle C90-270 (°) | 24        |
| UGRL                   | 8         |
| Efficiency (lm/W)      | 55        |



Beam Angle: 24°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2167  | 0.43 |
| 2    | 542   | 0.85 |
| 3    | 241   | 1.28 |
| 4    | 135   | 1.71 |
| 5    | 87    | 2.13 |


Luminous flux luminaire  
476 lm (EXTREME CUT OFF)

## Electrical

|              |                                                                                                                     |                  |         |
|--------------|---------------------------------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 35                                                                                                                  | Emergency        | Without |
| Current (mA) | 200                                                                                                                 | Insulation class | III     |
| Dimmable     | Yes                                                                                                                 |                  |         |
| Driver       | Remote excluded                                                                                                     |                  |         |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |         |

## Physical

|                     |       |                    |        |
|---------------------|-------|--------------------|--------|
| Color               | Black | Spot diameter (mm) | 59     |
| Orientation         | Fixed | Lifespan (L70 B10) | L80B50 |
| Trim                | yes   |                    |        |
| Recessed depth (mm) | 100   |                    |        |
| Weight (kg)         | 0.14  |                    |        |



## Easy Kap Ø 50 Fixed Optic Medium



Continuous current power supply.  
220/240V – 50/60Hz. Adjustable Current  
150 mA – 7,2W / 200 mA – 9,5W / 250 mA  
– 12W / 300 mA – 14,5W / 350 mA  
– 17W / 400 mA – 19,5W / 450 mA – 21,5W  
/ 500 mA – 24W. Mains or push dimming  
60.9421



Continuous current power supply, 0-  
10V dimmable, 220/240V – 50/60Hz,  
200mA – 20W  
60.9483



Continuous current power supply,  
dimmable DALI 2, 220/240V – 50/60Hz,  
200mA – 20W  
60.9604



Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200 mA – 8,5W /  
300 mA – 13W / 350 mA – 15W / 400 mA  
– 17,5W / 450 mA – 19,5W / 500 mA –  
22W  
60.9160



Casambi Controller 220-240V. Remote  
Installation  
60.9392