


## Easy Kap Ø 80 Adjustable Optic Flood - Dim-To-Warm

03.4172.GL.LE - Gold

Recessed luminaire with LED light source. 220-240V &amp; dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V &amp; dimmable 1-10V power supply included.




## Main specifications

Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	677
Power (W)	13W	Mountings	Ceiling recessed
System power (W)	13	Environment	Indoor dry location
CCT (K)	2850K-1800K		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	46
Beam angle C90-270 (°)	46
UGRL	14
Efficiency (lm/W)	52



Beam Angle: 46°

	h(m)	E(lx)	D(m)
1	1205	0.85	
2	301	1.71	
3	134	2.56	
4	75	3.41	
5	48	4.26	

Luminous flux luminaire  
677 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

## Physical

Color	Gold	Tilt (°)	20
Orientation	Adjustable	Rotation (°)	360
Trim	yes	Spot diameter (mm)	80
Recessed depth (mm)	91	Lifespan (L70 B10)	L80B50
Weight (kg)	0.24		

## Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

