


## Easy Kap Ø 80 Fixed Optic Flood - Dim-To-Warm

■ 03.4297.CU.LE - Copper

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




### Main specifications

Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	694
Power (W)	13W	Mountings	Ceiling recessed
System power (W)	13	Environment	Indoor dry location
CCT (K)	2850K-1800K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	46
Beam angle C90-270 (°)	46
UGRL	13
Efficiency (lm/W)	53



Beam Angle: 46°

	h(m)	E(lx)	D(m)
1	1174	0.86	
2	293	1.71	
3	130	2.57	
4	73	3.42	
5	47	4.28	

Luminous flux luminaire  
694 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

### Physical

Color	Copper	Spot diameter (mm)	80
Orientation	Fixed	Lifespan (L70 B10)	L80B50
Trim	yes		
Recessed depth (mm)	91		
Weight (kg)	0.24		

### Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

