


## Easy Kap Ø 80 Fixed Optic Medium Dali On Stock

03.4192.B1.CD - White

Recessed luminaire with LED light source. Remote 220/240V power supply included. Installation frame not necessary.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	630
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	26
<b>Beam angle C90-270 (°)</b>	26
<b>Efficiency (lm/W)</b>	68



<b>Beam Angle:</b>	26°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1868	0.46	
2	467	0.92	
3	208	1.39	
4	117	1.85	
5	75	2.31	

Luminous flux luminaire  
630 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Driver type</b>	Dimmable DALI 1
<b>Voltage (V)</b>	17.40	<b>Emergency</b>	Without
<b>Current (mA)</b>	500	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	80
<b>Orientation</b>	Fixed		
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	91		
<b>Weight (kg)</b>	0.24		

### Note

Diffusing lens included

