


Easy Kap Ø 80 Fixed Optic Medium On Stock

■ 03.4192.GL.DF - Gold

Recessed luminaire with LED light source. Remote 220/240V power supply included. Installation frame not necessary.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 618 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 26 |
| Beam angle C90-270 (°) | 26 |
| Efficiency (lm/W) | 67 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 26° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 2003 | 0.46 | |
| 2 | 501 | 0.92 | |
| 3 | 223 | 1.38 | |
| 4 | 125 | 1.84 | |
| 5 | 80 | 2.30 | |

Luminous flux luminaire
618 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|--------------|
| Frequency (Hz) | 50/60 | Driver type | Non Dimmable |
| Voltage (V) | 17.40 | Emergency | Without |
| Current (mA) | 500 | Insulation class | II |
| Dimmable | No | | |
| Driver | Remote included | | |

Physical

| | | | |
|----------------------------|-------|---------------------------|----|
| Color | Gold | Spot diameter (mm) | 80 |
| Orientation | Fixed | | |
| Trim | yes | | |
| Recessed depth (mm) | 91 | | |
| Weight (kg) | 0.24 | | |

Note

Diffusing lens included

