




## Easy Kap Ø 80 Plus Adjustable Optic Flood

Update

### 05.7405.BU - Blue

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Diffusing lens included.




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 906                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 13.4W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 54        |
| Beam angle C90-270 (°) | 54        |
| Efficiency (lm/W)      | 67        |



|             |       |      |  |
|-------------|-------|------|--|
| Beam Angle: | 54°   |      |  |
| h(m)        | E(lx) | D(m) |  |
| 1           | 1414  | 1.01 |  |
| 2           | 353   | 2.03 |  |
| 3           | 157   | 3.04 |  |
| 4           | 88    | 4.05 |  |
| 5           | 57    | 5.07 |  |

Luminous flux luminaire  
906 lm (EXTREME CUT OFF)

### Electrical

|              |   |                  |         |
|--------------|---|------------------|---------|
| Voltage (V)  | 17,8  | Emergency        | Without |
| Current (mA) | 700   | Insulation class | III     |
| Dimmable     | Yes   |                  |         |
| Driver       | Remote excluded   |                  |         |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                  |         |

### Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Blue       | Tilt (°)           | 20  |
| Orientation         | Adjustable | Rotation (°)       | 360 |
| Trim                | yes        | Spot diameter (mm) | 80  |
| Recessed depth (mm) | 150        |                    |     |
| Weight (kg)         | 0,241      |                    |     |

## Easy Kap Ø 80 Plus Adjustable Optic Flood



---

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



---

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/650/700/750/800/850/900 mA – 15W.  
60.9188



---

Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W  
60.9467



---

Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2  
60.9222



---

Non dimmable continuous current power supply. 15-30W, 220/240V – 50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



---

Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable switch. 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.  
60.8847