

Easy Kap Ø 80 Wall-Washer - Dim-To-Warm

■ 03.4196.GL.LE - Gold

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	718
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13W	Environment	Indoor dry location
CCT (K)	2850K-1800K		
CRI	95		

Optical

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	27
Beam angle C90-270 (°)	36
Efficiency (lm/W)	55



Beam Angle: 27°

h(m) E(lx) D(m)

1 1289 0.63

2 322 1.25

3 143 1.88

4 81 2.50

5 52 3.13

Luminous flux luminaire
718 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33.00	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Gold	Spot diameter (mm)	80
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	81		
Weight (kg)	0.24		

Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

