

## Easy Kap Ø105 Fixed Optic Flood

■ 05.7007.BU - Blue


Recessed luminaire with LED light source. Remote transformer not included. Installation frame not necessary.

### Main specifications

|                  |       |                |                  |
|------------------|-------|----------------|------------------|
| Number of heads  | 1     | CRI            | 90               |
| Lamp category    | LED   | Net lumen (lm) | 2326             |
| Power (W)        | 25.9W | Mountings      | Ceiling recessed |
| System power (W) | 25.9  | Environment    | Indoor           |
| CCT (K)          | 3000K |                |                  |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 53        |
| Beam angle C90-270 (°) | 53        |
| Efficiency (lm/W)      | 89        |



Beam Angle: 53°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 3462  | 1.01 |
| 2    | 866   | 2.01 |
| 3    | 385   | 3.02 |
| 4    | 216   | 4.03 |
| 5    | 138   | 5.04 |

Luminous flux luminaire  
2326 lm (EXTREME CUT OFF)

### Electrical

|              |                                                                                            |                  |         |
|--------------|--------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 34                                                                                         | Emergency        | Without |
| Current (mA) | 650                                                                                        | Insulation class | III     |
| Dimmable     | Yes                                                                                        |                  |         |
| Driver       | Remote                                                                                     |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |         |

### Physical

|                     |       |                    |     |
|---------------------|-------|--------------------|-----|
| Color               | Blue  | Spot diameter (mm) | 111 |
| Orientation         | Fixed |                    |     |
| Trim                | yes   |                    |     |
| Recessed depth (mm) | 150   |                    |     |
| Weight (kg)         | 0,55  |                    |     |

## Easy Kap Ø105 Fixed Optic Flood



---

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable  
60.9592



---

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 36W – 700 mA  
60.9439



---

Continuous current supply source of 240V – 50/60Hz with dimmable DALI 2  
60.9186



---

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207