

## Easy Kap Ø105 Fixed Optic Medium

■ 05.7001.BU - Blue


Recessed luminaire with LED light source. Remote transformer not included. Installation frame not necessary.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1596
Power (W)	25.9W	Mountings	Ceiling recessed
System power (W)	25.9	Environment	Indoor
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27



Beam Angle: 27°

h(m)	E(lx)	D(m)
1	6048	0.47
2	1512	0.94
3	672	1.41
4	378	1.89
5	242	2.36

Luminous flux luminaire  
1596 lm (EXTREME CUT OFF)

### Electrical

Voltage (V)	34	Emergency	Without
Current (mA)	650	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Certification / Marking



### Physical

Color	Blue	Spot diameter (mm)	111
Orientation	Fixed	Length (mm)	111
Trim	yes		
Recessed depth (mm)	150		
Weight (kg)	0,55		

## Easy Kap Ø105 Fixed Optic Medium



---

Continuous current supply source of  
240V – 50/60Hz with dimmable DALI 2  
60.9186



---

Continuous current power supply, 0/1-  
10V dimmable, 220/240V – 50/60Hz,  
36W – 700 mA  
60.9439



---

Power supply Casambi. 21.5W-32W  
60.9207



---

Continuous current power supply.  
Power current selected through  
adjustable. 13-42W  
60.9162