


Easy Kap Ø105 Wall-Washer

■ 05.7021.GL - Gold

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Installation frame not necessary.

Recessed luminaire with LED light source. Remote electronic transformer 220/240V not included. Installation frame not necessary.



Main specifications

| | | | |
|-------------------------|-------|--------------------|------------------|
| Number of heads | 1 | CRI | 90 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 23W | Environment | Indoor |
| System power (W) | 25.9 | | |
| CCT (K) | 3000K | | |

Optical

| | | | |
|---------------------------|-------------|---------------------------|----|
| Lighting type | Direct | Beam angle C90-270 | 33 |
| LED type | LED array | (°) | |
| Light distribution | Asymmetric | | |
| Optical type | Wall-washer | | |
| Beam angle (°) | 26 | | |

Electrical

| | | | |
|---------------------|--|-------------------------|---------|
| Voltage (V) | 34 | Emergency | Without |
| Current (mA) | 650 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | remote excluded | | |
| Driver type | Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI | | |

Physical

| | | | |
|----------------------------|-------|---------------------------|-----|
| Color | Gold | Spot diameter (mm) | 111 |
| Orientation | Fixed | Length (mm) | 111 |
| Trim | yes | | |
| Recessed depth (mm) | 134 | | |
| Weight (kg) | 0,53 | | |

Certification / Marking



Easy Kap Ø105 Wall-Washer



Continuous current supply source of
240V – 50/60Hz with dimmable DALI 2
60.9186



Continuous current power supply, 0/1-
10V dimmable, 220/240V – 50/60Hz,
36W – 700 mA
60.9439



Power supply Casambi. 21.5W-32W
60.9207



Continuous current power supply.
Power current selected through
adjustable. 13-42W
60.9162