


Easy Kap Ø50 Adjustable Optic Flood

■ 05.7212.CU - Copper

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

Number of heads	1	Net lumen (lm)	472
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	7.5W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	49
Beam angle C90-270 (°)	49



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	717	0.91
2	179	1.83
3	80	2.74
4	45	3.66
5	29	4.57

Luminous flux luminaire
472 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	35	Emergency	Without
Current (mA)	200	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

Certification / Marking



Physical

Color	Copper	Tilt (°)	20
Orientation	Adjustable	Rotation (°)	360
Trim	yes	Spot diameter (mm)	50
Recessed depth (mm)	91	Length (mm)	59
Weight (kg)	0,162		

Easy Kap Ø50 Adjustable Optic Flood




Power supply non dimmable.
Multicurrent 125-500mA; 5,5-22W
60.9160



Continuous current power supply
dimmable 0-10V. 20W
60.9483



Continuous current power supply
dimmable DALI 220/240V – 50/60Hz.
20W – 200 mA.
60.9604



Casambi Broadcast. Remote Installation
60.9392



Continuous current power supply of
7,2-24W, 220/240V – 50/60Hz
60.9421