


Easy Kap Ø50 Adjustable Optic Medium

■ 05.7216.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

Number of heads	1	Net lumen (lm)	476
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	7.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24
Efficiency (lm/W)	55



Beam Angle: 24°

h(m)	E(lx)	D(m)
1	2167	0.43
2	542	0.85
3	241	1.28
4	135	1.71
5	87	2.13

Luminous flux luminaire
476 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	35	Emergency	Without
Current (mA)	200	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

Physical

Color	Black	Tilt (°)	20
Orientation	Adjustable	Rotation (°)	360
Trim	yes	Spot diameter (mm)	59
Recessed depth (mm)	91		
Weight (kg)	0,162		



Easy Kap Ø50 Adjustable Optic Medium



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.
60.9160



Continuous current power supply dimmable 0-10V. 20W
60.9483



Continuous current power supply dimmable DALI 220/240V – 50/60Hz. 20W – 200 mA.
60.9604



Casambi Controller 220-240V. Remote Installation
60.9392



Continuous current power supply of 7,2-24W, 220/240V – 50/60Hz
60.9421