


## Easy Kap Ø50 Adjustable Optic Medium

05.7216.B1 - White

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	524
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	7.5W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	24
<b>Beam angle C90-270 (°)</b>	24



<b>Beam Angle: 24°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2183	0.43
2	546	0.86
3	243	1.30
4	136	1.73
5	87	2.16

Luminous flux luminaire  
524 lm (EXTREME CUT OFF)

### Electrical

<b>Voltage (V)</b>	35	<b>Emergency</b>	Without
<b>Current (mA)</b>	200	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

### Certification / Marking



### Physical

<b>Color</b>	White	<b>Tilt (°)</b>	20
<b>Orientation</b>	Adjustable	<b>Rotation (°)</b>	360
<b>Trim</b>	yes	<b>Spot diameter (mm)</b>	50
<b>Recessed depth (mm)</b>	91	<b>Length (mm)</b>	59
<b>Weight (kg)</b>	0,162		

## Easy Kap Ø50 Adjustable Optic Medium



---

Power supply non dimmable.  
Multicurrent 125-500mA; 5,5-22W  
60.9160



---

Continuous current power supply  
dimmable 0-10V. 20W  
60.9483



---

Continuous current power supply  
dimmable DALI 220/240V – 50/60Hz.  
20W – 200 mA.  
60.9604



---

Casambi Broadcast. Remote Installation  
60.9392



---

Continuous current power supply of  
7,2-24W, 220/240V – 50/60Hz  
60.9421