


## Easy Kap Ø50 Adjustable Optic Spot

05.7210.CU - Copper

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




## Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 547              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 7.5W  | Environment    | Indoor           |
| CCT (K)         | 2700K |                |                  |
| CRI             | 90    |                |                  |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |
| Efficiency (lm/W)      | 63        |



Beam Angle: 15°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 5630  | 0.26 |
| 2    | 1408  | 0.51 |
| 3    | 626   | 0.77 |
| 4    | 352   | 1.03 |
| 5    | 225   | 1.29 |

Luminous flux luminaire  
547 lm (EXTREME CUT OFF)

## Electrical

|              |                                                                                            |                  |         |
|--------------|--------------------------------------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 35                                                                                         | Emergency        | Without |
| Current (mA) | 200                                                                                        | Insulation class | III     |
| Dimmable     | Yes                                                                                        |                  |         |
| Driver       | Remote                                                                                     |                  |         |
| Driver type  | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |         |

## Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Copper     | Tilt (°)           | 20  |
| Orientation         | Adjustable | Rotation (°)       | 360 |
| Trim                | yes        | Spot diameter (mm) | 59  |
| Recessed depth (mm) | 91         |                    |     |
| Weight (kg)         | 0,162      |                    |     |



## Easy Kap Ø50 Adjustable Optic Spot



Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200mA – 8,5W / 250mA – 11W / 300mA – 13W / 350mA – 15W / 400mA – 17,5W / 450mA 19,5W / 500mA – 22W.  
60.9160



Continuous current power supply dimmable 0-10V. 20W  
60.9483



Continuous current power supply dimmable DALI 220/240V – 50/60Hz. 20W – 200 mA.  
60.9604



Casambi Controller 220-240V. Remote Installation  
60.9392



Continuous current power supply of 7,2-24W, 220/240V – 50/60Hz  
60.9421