


Easy Kap Ø50 Fixed Optic Flood

■ 05.7202.CU - Copper

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

| | | | |
|-----------------|-------|----------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 472 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 7.5W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 49 |
| Beam angle C90-270 (°) | 49 |



Beam Angle: 49°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 717 | 0.91 |
| 2 | 179 | 1.83 |
| 3 | 80 | 2.74 |
| 4 | 45 | 3.66 |
| 5 | 29 | 4.57 |

Luminous flux luminaire
472 lm (EXTREME CUT OFF)

Electrical

| | | | |
|--------------|--|------------------|---------|
| Voltage (V) | 35 | Emergency | Without |
| Current (mA) | 200 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI | | |

Certification / Marking



Physical

| | | | |
|---------------------|--------|--------------------|----|
| Color | Copper | Spot diameter (mm) | 50 |
| Orientation | Fixed | Length (mm) | 59 |
| Trim | yes | | |
| Recessed depth (mm) | 100 | | |
| Weight (kg) | 0,136 | | |

Easy Kap Ø50 Fixed Optic Flood



Power supply non dimmable.
Multicurrent 125-500mA; 5,5-22W
60.9160



Continuous current power supply
dimmable 0-10V. 20W
60.9483



Continuous current power supply
dimmable DALI 220/240V – 50/60Hz.
20W – 200 mA.
60.9604



Casambi Broadcast. Remote Installation
60.9392



Continuous current power supply of
7,2-24W, 220/240V – 50/60Hz
60.9421