


Easy Kap Ø50 Fixed Optic Spot

■ 05.7205.74 - Black

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




Main specifications

Number of heads	1	Net lumen (lm)	567
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	7.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	5905	0.26
2	1476	0.52
3	656	0.77
4	369	1.03
5	236	1.29

Luminous flux luminaire
567 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	35	Emergency	Without
Current (mA)	200	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		

Certification / Marking



Physical

Color	Black	Spot diameter (mm)	50
Orientation	Fixed	Length (mm)	59
Trim	yes		
Recessed depth (mm)	100		
Weight (kg)	0,136		

Easy Kap Ø50 Fixed Optic Spot




Power supply non dimmable.
Multicurrent 125-500mA; 5,5-22W
60.9160



Continuous current power supply
dimmable 0-10V. 20W
60.9483



Continuous current power supply
dimmable DALI 220/240V – 50/60Hz.
20W – 200 mA.
60.9604



Casambi Broadcast. Remote Installation
60.9392



Continuous current power supply of
7,2-24W, 220/240V – 50/60Hz
60.9421