


## Easy Kap Ø80 Adjustable Optic Spot

■ 03.4153.BU - Blue

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	625
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	18
<b>Beam angle C90-270 (°)</b>	18



<b>Beam Angle:</b>	18°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2644	0.32	
2	661	0.65	
3	294	0.97	
4	165	1.30	
5	106	1.62	

Luminous flux luminaire  
625 lm (EXTREME CUT OFF)

### Electrical

<b>Voltage (V)</b>	17.80	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		


### Physical

<b>Color</b>	Blue	<b>Tilt (°)</b>	20
<b>Orientation</b>	Adjustable	<b>Rotation (°)</b>	360
<b>Trim</b>	yes	<b>Spot diameter (mm)</b>	80
<b>Recessed depth (mm)</b>	91		
<b>Weight (kg)</b>	0.24		

### Note

Diffusing lens included

### Certification / Marking



## Easy Kap Ø80 Adjustable Optic Spot



---

Power supply non dimmable.  
Multicurrent 125-500mA; 5,5-22W  
60.9160



---

Continuous current power supply of  
13-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. Synchronisation  
cables not included.  
60.9188



---

Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847



---

Continuous current power supply of  
12-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable. Reguable DALI 1 y DALI 2  
60.9222



---

Continuous current power supply,  
Mains dimming , 220/240V – 50/60Hz,  
10W – 500mA.  
60.9411



---

Power supply Casambi. 21.5W-32W  
60.9207