

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Number of heads	1	Net lumen (lm)	696
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13W	Environment	Indoor

CCT (K) 2850K-1800K

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	19
Beam angle C90-270 (°)	19
Efficiency (lm/W)	53



Luminous flux luminaire 696 lm (EXTREME CUT OFF)

Bear	Beam Angle:	
h(m)	E(lx)	D(m)
1	2879	0.33
2	720	0.67
3	320	1.00
4	180	1.33
5	115	1 67





Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	33.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic		

dimmable 1-10V



Physical

•		
Color	Gold	Spot diameter (mm) 80
Orientation	Fixed	
Trim	yes	
Recessed depth (mm)	91	
Weight (kg)	0.24	

Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.