



03.4196.B1.LE - White

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Number of heads1Net lumen (lm)770Lamp categoryLEDMountingsCeiling recessedPower (W)13WEnvironmentIndoor

CCT (K) 2850K-1800K CRI 95

Optical

Lighting type Indirect, Direct
LED type LED array
Light distribution Asymmetric
Optical type Wall-washer
Beam angle (°) 28
Beam angle C90-270 (°) 37
Efficiency (Im/W) 59



Luminous flux luminaire 770 lm (EXTREME CUT OFF)

Beam Angle:		28°
h(m)	E(lx)	D(m
1	1240	0.64
2	310	1.29
3	138	1.93
4	78	2.58
5	50	3 22

770 lm (EXTREME

Electrical

Frequency (Hz) 50/60 Emergency Without Voltage (V) 33.00 Insulation class II

Dimmable Yes

Driver Remote

Driver type Electronic

dimmable 1-10V



ColorWhiteSpot diameter (mm)80OrientationFixedTrimyesRecessed depth (mm)81Weight (kg)0.24

Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.

