






03.4196.BU.LE - Blue

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Number of heads1Net lumen (lm)672Lamp categoryLEDMountingsCeiling recessedPower (W)13WEnvironmentIndoor

CCT (K) 2850K-1800K CRI 95

Optical

Lighting type Indirect, Direct
LED type LED array
Light distribution Asymmetric
Optical type Wall-washer
Beam angle (°) 28
Beam angle C90-270 (°) 29
Efficiency (Im/W) 51



Luminous flux luminaire 672 lm (EXTREME CUT OFF)

Without

Beam Angle:		28°
h(m)	E(l ×)	D(m)
1	1270	0.65
2	317	1.30
3	141	1.96
4	79	2.61
5	51	3 26



Electrical

Frequency (Hz) 50/60 Emergency
Voltage (V) 33.00 Insulation class
Dimmable Yes
Driver Remote
Driver type Electronic



Physical

ColorBlueSpot diameter (mm)80OrientationFixedTrimyesRecessed depth (mm)81Weight (kg)0.24

dimmable 1-10V

Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens included.