

## Easy Kap Ø80 Wall-Washer - Dim-To-Warm



Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Number of heads Net lumen (lm) 718 LED Ceiling recessed Lamp category Mountings Power (W) 13W **Environment** Indoor

2850K-1800K CCT (K) CRI

Optical

Lighting type Indirect, Direct LED type LED array Light distribution Asymmetric Optical type Wall-washer Beam angle (°) 27 Beam angle C90-270 (°) 36 Efficiency (lm/W) 55



Luminous flux luminaire 718 lm (EXTREME CUT OFF)

Beam Angle:		27°
h(m)	E( <b>l</b> ×)	D(m
1	1289	0.63
2	322	1.25
3	143	1.88
4	81	2.50
5	52	2 13



Frequency (Hz) 50/60 **Emergency** Without Voltage (V) 33.00 Insulation class Dimmable Yes Driver Remote Electronic

dimmable 1-10V



## **Physical**

Driver type

Color Gold Spot diameter (mm) 80 Orientation Fixed Trim yes Recessed depth (mm) 81 Weight (kg) 0.24

## Note

For 110V PSU versions, please consult with the front office. Installation frame not necessary. Diffusing lens