15°

D(m) 0.26

0.52

0.77

1.03

1.29

Beam Angle:

h(m) E(lx)

2

3

1922

481

214 120

77







09.3801.40A - White

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.


Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	169
Power (W)	3.5W	Mountings	Track
		- .	

System power (W) Indoor dry location 3.5 **Environment** CCT (K) 2700K

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15
UGRL	2
Efficiency (lm/W)	48.29




/ ,		\ \/	4	
)° \	1922 cd	30°	5	
mino	us flux I	uminaire		

Without

Lui 169 lm

20

















Electrical

Voltage (V)	24
Current (mA)	250
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Non Dimmable,
	Dimmable
	Casambi,
	Dimmable 1-
	10V, Dimmable

III	
	III

Emergency

Physical

Color	White	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

DALI 1

Note

Accessories included (honeycomb and screening crosspiece).