



## Find Me 0

### 09.3803.06A - Chrome


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	160
Power (W)	3.5W	Mountings	Track
System power (W)	3.5	Environment	Indoor dry location
CCT (K)	2700K		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	25
UGRL	1
Efficiency (lm/W)	45.71



Beam Angle: 25°

h(m) E(lx) D(m)

1 828 0.45


2 207 0.89

3 92 1.34

4 52 1.79

5 33 2.23

Luminous flux luminaire  
160 lm



## Electrical

Voltage (V)	24	Emergency	Without
Current (mA)	250	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		

## Physical

Color	Chrome	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		

## Note

Accessories included (honeycomb and screening crosspiece).

