



## Find Me 0

■ 09.3803.14 - Black


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

## Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 179    |
| Lamp category   | LED   | Mountings      | Track  |
| Power (W)       | 3.5W  | Environment    | Indoor |
| CCT (K)         | 2700K |                |        |
| CRI             | 90    |                |        |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 26        |



Beam Angle: 26°

h(m) E(lx) D(m)

1 929 0.45


2 232 0.89

3 103 1.34

4 58 1.79

5 37 2.23

Luminous flux luminaire  
179 lm



## Electrical

|             |                                                                                                           |                  |     |
|-------------|-----------------------------------------------------------------------------------------------------------|------------------|-----|
| Voltage (V) | 24.00                                                                                                     | Insulation class | III |
| Dimmable    | Yes                                                                                                       |                  |     |
| Driver      | Remote                                                                                                    |                  |     |
| Driver type | Electronic,<br>Electronic dimmable<br>CASAMBI,<br>Electronic dimmable 1-<br>10V, Electronic dimmable DALI |                  |     |
|             | Without                                                                                                   |                  |     |

## Emergency

## Physical

|              |            |                    |    |
|--------------|------------|--------------------|----|
| Color        | Black      | Spot diameter (mm) | 24 |
| Orientation  | Adjustable | Length (mm)        | 24 |
| Weight (kg)  | 0.06       |                    |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

## Note

Accessories included (honeycomb and screening crosspiece).

