



Find Me 0 Casambi integrated





09.3900.06 - Chrome


Main specifications

Number of heads	1
Lamp category	LED
Power (W)	3.5W
CCT (K)	3000K
CRI	90

Net lumen (lm) 183 Mountings Track Environment Indoor

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Insulation class

Beam Angle: 15° h(m) = E(Ix)D(m) 1917 0.26 479 0.52 3 213 0.77 4 120 1.03 77 1.29

	 81		
67,5	ø24	20	95

	757	IΡ
GD	lacksquare	20

-	lectrical
_	

voitage (v)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmahla

Electronic dimmable CASAMBI Without

Emergency Physical

Color Orientation	Chrome Adjustable	Spot diameter (mm) Length (mm)	24 24
Weight (kg)	0.06		
Tilt (°) Rotation (°)	90 360		

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)