









09.3900.40A - White

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


Main specifications


Number of heads	1
Lamp category	LED
Power (W)	3.5W
CCT (K)	3000K
CRI	90

Net lumen (lm) 183 Mountings Track

Environment Indoor dry location







 $E(I_X)$ D(m) h(m) 2084 0.26 521 0.52 3 232 0.77 4 130 1.03 83 1.29

Beam Angle:

15°

Luminous
183 lm

Voltage (V)	24
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable
	Casambi
Emergency	Without

Insulation class



GWT 850°









20



95





Pl	nysical	

Color	White	Spot diameter (mm) 24
Orientation	Adjustable	Length (mm) 24
Weight (kg)	0.06	_
Tilt (°)	90	
Rotation (°)	360	

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

