







## 09.3900.40A - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.

## Main specifications

Number of heads	1	CRI
Lamp category	LED	Net lumen (lm)
Power (W)	3.5W	Mountings
System power (W)	3.5	Environment
CCT (K)	3000K	

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15
UGRL	2
Efficiency (lm/W)	52.29



90

183

Track

Indoor dry location

Beam Angle: 15°  $E(I_X)$ D(m) h(m) 2084 0.26 521 0.52 3 232 0.77 4 130 1.03 83 1.29

=1	
Electrical	

Voltage (V)	24	Emergency	Without
Current (mA)	250	Insulation class	III
Dimmable	Yes		
Driver	Remote		
	excluded		
Driver type	Dimmahla		

Casambi

## **Physical**

Color	White	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06	Lifespan (L70 B10)	L80B50
Tilt (°)	90		
Rotation (°)	360		



Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



