



# Find Me 0 Casambi integrated





#### 09.3901.06 - Chrome


## Main specifications

Number of heads	1
_amp category	LED
Power (W)	3.5W
CCT (K)	2700K
CRI	90

Net lumen (lm) 169 Mountings Track Environment Indoor

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Insulation class

Beam Angle: 15° h(m) = E(Ix)D(m) 1768 0.26 442 0.52 3 196 0.77 4 111 1.03 71 1.29

	 01		
1	Ī	, 1	Ī
2'29		20	95
9	ø24		
	ø24		

$\bigcirc$	\F7	<b>I</b> P
<b>GL</b>	lacksquare	20

voitage (v)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	dimmahla

Electronic dimmable CASAMBI Without

Emergency Withou

### Physical

Color	Chrome	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06		
Tilt (°)	90		
Rotation (°)	360		

#### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)