

## Find Me 0 Casambi integrated

New

## ■ 09.3901.14A - Black

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




## Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 169                 |
| Power (W)        | 3.5W  | Mountings      | Track               |
| System power (W) | 3.5   | Environment    | Indoor dry location |
| CCT (K)          | 2700K |                |                     |

## Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 15        |
| Beam angle C90-270 (°) | 15        |
| UGRL                   | 2         |
| Efficiency (lm/W)      | 48.29     |



Beam Angle: 15°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 1922 | 0.26  |      |
| 2 | 481  | 0.52  |      |
| 3 | 214  | 0.77  |      |
| 4 | 120  | 1.03  |      |
| 5 | 77   | 1.29  |      |

Luminous flux luminaire  
169 lm



## Electrical

|              |                 |                  |         |
|--------------|-----------------|------------------|---------|
| Voltage (V)  | 24              | Emergency        | Without |
| Current (mA) | 250             | Insulation class | III     |
| Dimmable     | Yes             |                  |         |
| Driver       | Remote excluded |                  |         |
| Driver type  | Dimmable        |                  |         |
|              | Casambi         |                  |         |

## Physical

|              |            |                    |        |
|--------------|------------|--------------------|--------|
| Color        | Black      | Spot diameter (mm) | 24     |
| Orientation  | Adjustable | Length (mm)        | 24     |
| Weight (kg)  | 0.06       | Lifespan (L70 B10) | L80B50 |
| Tilt (°)     | 90         |                    |        |
| Rotation (°) | 360        |                    |        |

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

