







#### 09.3902.14A - Black

 ${\sf LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.

## Main specifications


Number of heads	1
Lamp category	LED
Power (W)	3.5W
System power (W)	3.5
CCT (K)	3000K

CRI 90 Net lumen (lm) 194 Mountings Track

Environment Indoor dry location

### Optical

Direct
Power LED
Symmetric
Medium
25
25
2
55.43



 $E(I_X)$ D(m) h(m) 1007 0.45 252 0.89 3 112 1.34 1.79 4 63 40 2.23

Beam Angle:

25°

Luitiitious iiux
194 <b>l</b> m

#### Electrical

Voltage (V)	24
Current (mA)	250
Dimmable	Yes
Driver	Remote
	excluded
Driver type	Dimmable
	Casamhi

**Emergency** Without Insulation class

> 24 L80B50

# Physical

Color	Black	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06	Lifespan (L70 B10)	L80
Tilt (°)	90		
Rotation (°)	360		

#### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



