









09.3902.40 - White

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.

## Main specifications


Number of heads	1
Lamp category	LED
Power (W)	3.5W
CCT (K)	3000K
CRI	90

Net lumen (lm) 194 Mountings Track Environment

Indoor

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	26
Beam angle C90-270 (°)	26



Beam Angle: 25°  $E(I_X)$ D(m) h(m) 1007 0.45 252 0.89 3 112 1.34 4 1.79 63 40 2.23

Electrical	
Voltage (V)	

/oltage (V)	24.00
Dimmable	Yes
Oriver	Remote
Oriver type	FLOS smart
	control,
	Electronic
	althoraca a la la

Insulation class







20

95

Dimmable	Yes			
Driver	Remote			
Driver type	FLOS smart			
	control,			
	Electronic			
	dimmable			
	CASAMBI			
Emergency	Without			
Physical				
Color	White	Spot diameter (mm)	24	
•	White Adjustable	Spot diameter (mm) Length (mm)	24 24	
Color				
Color Orientation	Adjustable			

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)