


## Find Me 0 Casambi integrated

New

### 09.3902.CZA - Bronze

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




### Main specifications

Number of heads	1	Net lumen (lm)	194
Lamp category	LED	Mountings	Track
Power (W)	3.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle:	25°		
	h(m)	E(lx)	D(m)
1	1007	0.45	
2	252	0.89	
3	112	1.34	
4	63	1.79	
5	40	2.23	

Luminous flux luminaire  
194 lm

### Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

### Physical

Color	Bronze	Spot diameter (mm)	24
Orientation	Adjustable	Length (mm)	24
Weight (kg)	0.06		
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

