



## Find Me 0 Casambi integrated





### 09.3903.06 - Chrome

 ${\sf LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


### Main specifications

Number of heads	1
Lamp category	LED
Power (W)	3.5W
CCT (K)	2700K
CRI	90

Net lumen (lm) 179 Mountings Track Environment Indoor

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	26
Beam angle C90-270 (°)	26



Beam Angle: 25° E(Ix)D(m) h(m) 1 828 0.45 2 207 0.89 3 92 1.34 4 1.79 52 33 2.23

Luminous flux lumi
160 lm

#### Electrical

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic
	10 1 1

dimmable CASAMBI Without

**Emergency** 

# Insulation class

Physical

Orientation Weight (kg) 0.06 Tilt (°) 90 360 Rotation (°)

Chrome Spot diameter (mm) 24 Adjustable

Length (mm)



Color

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

