


Find Me 0 Casambi integrated

New

09.3903.14A - Black

LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Casambi via Flos Control App to individually control the lights.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 179 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 3.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 25° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 929 | 0.45 | |
| 2 | 232 | 0.89 | |
| 3 | 103 | 1.34 | |
| 4 | 58 | 1.79 | |
| 5 | 37 | 2.23 | |

Luminous flux luminaire
179 lm

Electrical

| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable | | |
| Emergency | Casambi | | |
| | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|----|
| Color | Black | Spot diameter (mm) | 24 |
| Orientation | Adjustable | Length (mm) | 24 |
| Weight (kg) | 0.06 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)

