









09.3903.40 - White


## Main specifications

| Number of heads | 1     |
|-----------------|-------|
| Lamp category   | LED   |
| Power (W)       | 3.5W  |
| CCT (K)         | 2700K |
| CRI             | 90    |
|                 |       |

Net lumen (lm) 179 Mountings Track Environment Indoor



| Lighting type          | Direct    |
|------------------------|-----------|
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 26        |
| Beam angle C90-270 (°) | 26        |
|                        |           |



Insulation class

Beam Angle: 25° E(Ix)D(m) h(m) 929 0.45 232 0.89 3 103 1.34 1.79 4 58 37 2.23

| Lummous        |
|----------------|
| 179 <b>l</b> m |
|                |

## **Electrical**

| Voltage (V) | 24.00      |
|-------------|------------|
| Dimmable    | Yes        |
| Driver      | Remote     |
| Driver type | FLOS smart |
|             | control,   |
|             | Electronic |
|             | dimmahla   |

Electronic dimmable CASAMBI Without

Emergency

## Physical

| Color        | White      | Spot diameter (mm) | 24 |
|--------------|------------|--------------------|----|
| Orientation  | Adjustable | Length (mm)        | 24 |
| Weight (kg)  | 0.06       | _                  |    |
| Tilt (°)     | 90         |                    |    |
| Rotation (°) | 360        |                    |    |

## Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)



