





09.3810.40 - White


LED accent lighting module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via Casambi driver, 1–10-V or DALI in broadcast mode. To individually control the lights, select integrated Casambi versions.

Main specifications

Number of heads	1	Net lumen (lm)	314
Lamp category	LED	Mountings	Track
Power (W)	5.5W	Environment	Indoo
CCT (K)	3000K		
CRI	90		



Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Luminous flux luminaire 314 lm

Insulation class

Beam Ang l e:		14°
h(m) E(l×)	D(m)
1	4193	0.24
2	1048	0.49
3	466	0.73
4	262	0.97
5	168	1.21







Electrical

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	Electronic,
	Electronic
	dimmable
	CASAMBI,
	Electronic
	dimmable :
	10V, Electro

Emergency

Physical

Color	White	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.11		
Tilt (°)	90		
Rotation (°)	360		

dimmable DALI

Without

Note

Accessories included (honeycomb and screening crosspiece).