









#### 09.3910.CZ - Bronze

 ${\tt LED\ accent\ lighting\ module\ to\ be\ installed\ in\ the\ Zero\ Track\ system.\ Incorporated\ DC/DC\ electronic\ converter.}$ Casambi via Flos Control App to individually control the lights.


## Main specifications

Number of heads	1
amp category	LED
Power (W)	5.5W
CCT (K)	3000K
CRI	90

Net lumen (lm) 314 Mountings Track Environment Indoor

# Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Insulation class

Beam Angle: 14° h(m) = E(Ix)D(m) 4193 0.24 1048 0.49 3 466 0.73 4 262 0.97 168 1.21

	Lummous
	314 lm

#### Electrical

Voltage (V)	24.00
Dimmable	Yes
Driver	Remote
Driver type	FLOS smart
	control,
	Electronic

dimmable CASAMBI Without

**Emergency** 

# Physical

Color	Bronze	Spot diameter (mm)	33
Orientation	Adjustable	Length (mm)	33
Weight (kg)	0.11	_	
Tilt (°)	90		
Rotation (°)	360		

### Note

Accessories included (honeycomb and screening crosspiece). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi. Other types of regulation are broadcast (all lights are regulated at the same time)





